
High Profile Laminate SBS Class 4 Impact Shingles













Regions that are prone to algae growth should inquire about our Legacy® shingles featuring the Scotchgard $^{\!\scriptscriptstyle{\text{TM}}}$ protection from 3M. The Legacy $^{\!\scriptscriptstyle{\text{(S)}}}$ shingles, featuring











the 20-year Scotchgard™ Algae Resistant Roofing System warranty from 3M, are



Malarkey's revolutionary Legacy® shingle technology begins with a durable base layer of fiberglass mat. Malarkey's unique fiberglass mat is coated on both sides with SBS enhanced asphalt, which provides tensile strength and increased flexibility,









RUGGED DURABILITY



One of the most critical aspects of a successful roofing project is correct shingle installation. Improper fastener placement is the leading cause of incorrect shingle

Legacy® is manufactured using the patented ZONE® technology that includes a tapered nailing area over three times larger than other laminate shingles. The ZONE's® larger nailing area dramatically improves correct fastener placement.

installation and can subsequently void the warranty.























The SEBS asphalt has elongation capabilities up to 800 percent and is flexible down to 0°F (-18°C). The rain seal remains intact through the freeze and thaw cycle. Malarkey's SEBS asphalt adhesive is superior to oxidized asphalt because of its cohesive and adhesive properties. The adhesive properties of SEBS asphalt join the shingle together while the cohesive properties prevent it from breaking apart from







LIMITED WIND WARRANTY

Legacy® shingles come with a 110 mph (177 kph) Limited Wind Warranty.

ENHANCED WIND WARRANTY

Legacy® shingles are eligible for a 130 mph (209 kph) Enhanced Wind Warranty when Malarkey's Smart Start™ shingle is installed, shingles are six nailed, and one or more of Malarkey's supporting products - Arctic Seal[®], Right Start[™] UDL, SecureStart, EZ-Ridge (8", 10") or Hip & Ridge Strips (10", 12")**- are used.



FEATURING

- · Limited Lifetime Shingle Warranty
- 15-year Right Start[™] Warranty

TEST COMPLIANCE

- · ASTM D7158 Class H
- · ASTM D3161 Class F
- ASTM E108 Class A
- CSA A123.5
- FBC Approval #14809
- ASTM D3462
- ASTM D3018 Type I
- UL 2218 Class 4
- ICC Approval ESR 3150

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Limited warranties carry terms and conditions. Contact your local Malarkey representative for further information. See Malarkey Shingle Warranty for details.

 δ For complete Limited Lifetime Warranty details, reference Malarkey's Limited Lifetime Shingle Warranty. *Malarkey Roofing systems require algae resistant EZ-Ridge™ shingles or 10"&12" Hip and Ridge shingles, in conjunction with the algae resistant shingles, to receive the full 20-year algae resistant system warranty. The Alaskan® featuring Scotchgard™ Algae Resistant Protection from 3M can be substituted as hip and ridge shingles, in conjunction with the algae resistant shingles, to receive the full 20-year algae resistant system warranty. 3M and Scotchgard are trademarks of 3M Company. **Some contractors adapt roofing shingles for use as a hip and ridge shingle. If your contractor uses this method, the Enhanced Wind Warranty will apply when The Alaskan® is used as hip and ridge shingles. Use of Dura-Seal™ shingles for hip and ridge will not qualify toward Enhanced Wind Warranty.

Roofing Products Defining Excellence.™

P.O. BOX 17217, Portland, OR 97217 503.283.1191 | 800.545.1191 | Fax: 503.289.7644

WWW.MALARKEYROOFING.COM